

Technical Product Data



OC1203 ***Urethane Accelerated Reducer***

DESCRIPTION:

OC1203 Urethane Accelerator is a catalyst designed to accelerate the drying and cure times of 75 Series and 82 Series Topcoats and Clear Coats. This additive maintains excellent pot life stability while producing fast tack free and curing times.

TECHNICAL DATA

PACKAGED VOC	107 g/l, 0.89 lbs./gal
VOC AS USED AS DIRECTED	979 g/l, 8.16 lbs./gal
SHELF LIFE	one year (unopened)
FLASH POINT	-4° F, -20° C
RECOMMENDED DILUTION FOR USE	8 fluid ounces per gallon of activated Topcoat or Clear Coat

DIRECTIONS FOR USE:

Add up to 8 fluid ounces of OC1203 Urethane Accelerated Reducer per activated gallon of 75 or 82 Series Topcoats.

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Oceanair Coatings' experience and research and is believed to be reliable. As Oceanair Coatings has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.

090517

OCEANAIR PERFORMANCE COATINGS

4500 Williams Dr Suite 212-269 Georgetown, TX 78633

512.688.7607

www.oceanaircoatings.com