

# Technical Product Data



## **OC2115 Fisheye Eliminator**

### **DESCRIPTION:**

OC2115 Fisheye Eliminator is a very effective additive for preventing fisheyes, craters and other surface tension defects in the paint film caused by surface contamination. It is compatible with 75 Series, 82 Series Topcoats and Clear Coats.

### **TECHNICAL DATA**

PACKAGED VOC	809 g/l, 6.75 lbs./gal
VOC AS USED AS DIRECTED	6.32 g/l, 0.05 lbs./gal
SHELF LIFE	one year (unopened)
FLASH POINT	102° F, 39° C
RECOMMENDED DILUTION FOR USE	1 fluid ounce per gallon of activated Topcoat or Clear Coat

### **DIRECTIONS FOR USE:**

Add up to 1 fluid ounce or OC2115 Fisheye Eliminator per activated gallon of Topcoat or Clear Coat

**DISCLAIMER:** *The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Oceanair Coatings' experience and research and is believed to be reliable. As Oceanair Coatings has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*

060317

## **OCEANAIR PERFORMANCE COATINGS**

4500 Williams Dr Suite 212-269 Georgetown, TX 78633

512.688.7607

[www.oceanaircoatings.com](http://www.oceanaircoatings.com)