

Technical Data Sheet



OC2141 **Non Slip Clear Aggregate**

DESCRIPTION:

OC2141 Non Slip Aggregate can be added to Seaskid or any topcoat to provide additional slip resistance.

TECHNICAL DATA

PACKAGED VOC	0 g/l; 0 lbs/gal
PARTICLE SIZE AS PACKAGE	300 micron
SHELF LIFE	unlimited
FLASH POINT	none
RECOMMENDED USE LEVEL	3.2 oz, per gallon; 16 oz. per five-gallon pail; Do not add more than 8 oz per gallon.

DIRECTIONS FOR USE:

While continually stirring, add Clear Aggregate at the recommended rate. The product may float at first, but once it has wet out, it will mix well. Occasionally stir during application to ensure that the aggregate remains well suspended in the coating.

DISCLAIMER: *The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Oceanair Coatings experience and research and is believed to be reliable. As Oceanair Coatings has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.*

060317

OCEANAIR PERFORMANCE COATINGS

4500 Williams Drive, Suite 212-269 Georgetown, TX 78633
512.688.7607
www.oceanaircoatings.com