

## Technical Data Sheet



### OC1607 Urethane Retarder

#### DESCRIPTION:

OC1607 Urethane Retarder is a solvent retarder designed for use during hot and humid weather conditions. This Urethane Retarder is used in conjunction with Oceanair's 75 Series Buffable Polyurethane Topcoat and 94 & 96 Series Topcoats.

OC1607 Urethane Retarder:

- Increases wet edge times
- Retains excellent appearance of topcoat

#### TECHNICAL DATA:

PACKAGED VOC	810 grams/liter
POT LIFE OF MIXED GALLON	3 hours @70 °F (21°C)
SHELF LIKE	One year (unopened)
FLASH POINT	102°F (39°C)
RECOMMENDED USE LEVEL	Add 6 to 12 fluid ounces per activated gallon

#### DIRECTIONS FOR USE:

Add 6 to 12 fluid ounces of OC1607 Urethane Retarder per activated gallon of 75 Series Buffable Polyurethane Topcoat and 94 & 96 Series Topcoats.

**DISCLAIMER:** The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Oceanair Performance Coatings' experience and research, and is believed to be reliable. As Oceanair has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes. 06.2017

#### OCEANAIR Performance Coatings

4500 Williams Drive Suite 212-269  
Georgetown, TX, 78633  
512.688.7607

[www.oceanaircoatings.com](http://www.oceanaircoatings.com)